


## H05Z-K, H07Z-K



**Tip:** conductor pentru instalatii electrice.

**Simbol international:** H05Z-K, H07Z-K (VDE 0282)

**Tensiunea nominala :** 300/500 V, 450/750 V

**Domeniu de utilizare:** canale sau tuburi, dulapuri electrice, corpuri electrice.

### Constructia

**Conductor:** din cupru multifilar rasucit; **Izolatie speciala:** poliolefin – copolimerizat (HI3), nu contine halogen (fara degajare de gaze toxice sau corozive).

**Temperatura mediului ambiant:** -20 °C la +70 °C



### Parametri tehnici:

Sectiunea (mm <sup>2</sup> )	Culoarea	Diametrul exterior (mm)	Constructia (mm)	Masa cuprului (kg/km)	Masa totala (kg/km)
<b>H05Z-K 300/500 V</b>					
0,5	m,n,a,gr,v/g	2,4	16x0,21	5,0	9
0,75	m,n,a,gr,v/g	2,6	24x0,21	7,5	11
1	m,n,a,gr,v/g	2,8	32x0,21	10,0	14
<b>H07Z-K 450/750 V</b>					
1,5	m,n,a,gr,v/g	3,3	30x0,26	15	20
2,5	m,n,a,gr,v/g	3,8	50x0,26	25	30
4	m,n,a,gr,v/g	4,6	56x0,31	40	45
6	m,n,a,gr,v/g	5,2	84x0,31	60	65
10	m,n,a,gr,v/g	6,2	80x0,41	100	110
16	m,n,a,gr,v/g	7,1	128x0,41	160	170
25	n	10	200x0,41	250	260
35	n	11,9	280x0,41	350	360
50	n	13,7	400x0,41	500	510
70	n	16,4	356x0,51	700	710